

F1000PKS



At a glance

LIFTING		
manual	~	
Compact hydraulic system	~	
Hydrobull pump	×	
electric	×	

DRIVING	
manual	~
Steering handle	×
FaPo	×
electric	×

OPERATING FREQUENCY		
up to 10 times per month	~	
up to 25 times per month	×	
up to 100 times per month	×	
more than 100 times per month	×	

LIFTIN	IG CAPACITY WITH HORIZONTAL JIB	
/////////////////////////////////////	max. 1000 kg	~
3	500 kg at 1100 mm in front of the hydraulic system	~
	Note: NO Outreach in front of the wheels	

CHASSIS SHAPE		
Parallel	✓	
Splayed	×	
Foldable	✓	
dismountable	×	

Technical specifications

RATIO LIFTING CAPACITY, OUTREACH, LIFTING HEIGHT					
Jib	Lifting capacity/kg	Load with horizontal jib/mm		Lift height*/mm	
Position		in front of the hydraulic system approx.	in front of the wheels approx.	min.	max.
1	1000	800	-		2030
2	800	900	-		2130
3	700	1000	-		2230
4	500	1100	-		2330

^{*} at hook mouth opening - please refer to the diagram for the reduced outreach

OTHER DETAILS		min.	max.
Jib length from to		1120	1420
Length of chassis incl. wheels	mm		1825
Width of chassis external	mm		1000
Width of chassis internal/maximum	mm		850
Clearance height, jib lowered	mm		1750
Clearance	mm		145
Ground clearance	mm		30
Load wheel	mm		125
Steering wheel	mm		125
Weight	kg		130

▼ FEATURES

- · Lightweight crane for occasional use
- · Moved using push handles on the column
- · In idle periods, the chassis can be folded upwards in no time
- The machine stays folded and can be moved (without load)
- Highest lifting speed in its equipment class: Without load 80 mm lift per pump unit, with load 20 mm lift
- · single-acting pump
- · Incl. locking device on the steering wheels
- · Delivery with CE-declaration, no origin
- · Tested by us and recommended for occasional use
- · 2 Year Warranty





Not the right machine? No problem!

Fill out our form on www.hydrobull.de and we will happily produce a custom transport solution for you.

