



F1000VKS



Do you need an assembly or lifting aid from time to time and have a small budget?

Our foldable simple lightweight cranes are the best in their class!



At a glance

| LIFTING | |
|--------------------------|---|
| manual | ✓ |
| Compact hydraulic system | ✓ |
| Hydrobull pump | ✗ |
| electric | ✗ |

| DRIVING | |
|-----------------|---|
| manual | ✓ |
| Steering handle | ✓ |
| FaPo | ✗ |
| electric | ✗ |

| OPERATING FREQUENCY | |
|-------------------------------|---|
| up to 10 times per month | ✓ |
| up to 25 times per month | ✗ |
| up to 100 times per month | ✗ |
| more than 100 times per month | ✗ |

| LIFTING CAPACITY WITH HORIZONTAL JIB | | |
|---|--|---|
| | max. 1000 kg | ✓ |
| | 500 kg at 1090 mm in front of the hydraulic system | ✓ |
| Note: NO Outreach in front of the wheels | | |

| CHASSIS SHAPE | |
|---------------|---|
| Parallel | ✗ |
| Splayed | ✓ |
| Foldable | ✓ |
| dismountable | ✗ |

Technical specifications

RATIO LIFTING CAPACITY, OUTREACH, LIFTING HEIGHT

| Jib Position | Lifting capacity/kg | Load with horizontal jib/mm | | Lift height*/mm | |
|--------------|---------------------|--|--------------------------------|-----------------|------|
| | | in front of the hydraulic system approx. | in front of the wheels approx. | min. | max. |
| 1 | 1000 | 790 | – | | 2030 |
| 2 | 800 | 890 | – | | 2130 |
| 3 | 700 | 990 | – | | 2230 |
| 4 | 500 | 1090 | – | | 2330 |

* at hook mouth opening - please refer to the diagram for the reduced outreach

OTHER DETAILS

| | | min. | max. |
|-----------------------------------|----|------|------|
| Jib length from... to... | | 1120 | 1420 |
| Length of chassis incl. wheels | mm | | 1825 |
| Width of chassis external | mm | | 1170 |
| Width of chassis internal/maximum | mm | | 1020 |
| Clearance height, jib lowered | mm | | 1750 |
| Clearance | mm | | 145 |
| Ground clearance | mm | | 30 |
| Load wheel | mm | | 125 |
| Steering wheel | mm | | 125 |
| Weight | kg | | 130 |

FEATURES

- Lightweight crane for occasional use
- Moved using push handles on the column
- In idle periods, the chassis can be folded upwards in no time
- The machine stays folded and can be moved (without load)
- Highest lifting speed in its equipment class: Without load 80 mm lift per pump unit, with load 20 mm lift
- single-acting pump
- Incl. locking device on the steering wheels
- Delivery with CE-declaration, no origin
- Tested by us and recommended for occasional use
- 2 Year Warranty



**Not the right machine?
No problem!**

Fill out our form on www.hydrobull.de and we will happily produce a custom transport solution for you.

Link to www.hydrobull.de

Here, you can find more information incl. videos, photos etc.

