

L1500



At a glance

LIFTING	
manual	
Compact hydraulic system	~
Hydrobull pump	×
electric	×

DRIVING	
manual	~
Steering handle	×
FaPo	×
electric	×

OPERATING FREQUENCY	
up to 10 times per month	×
up to 25 times per month	~
up to 100 times per month	×
more than 100 times per month	×

LIFTING CAPACITY WITH HORIZONTAL JIB			
@	max. 1500 kg	✓	
3	max. 1500 kg at 1320 mm inside the chassis	✓	
	Note: NO Outreach in front of the wheels		

Parallel	✓
Splayed	×
Foldable	×

Parallel chassis

Technical specifications

* at hook mouth opening - please refer to the diagram for the reduced outreach

RATIO LIFTING CAPACITY, OUTREACH, LIFTING HEIGHT					
Jib	Lifting capacity/kg	Load with horizontal jib/mm		Lift height*/mm	
Position		in front of the hydraulic system approx.	in front of the wheels approx.	min.	max.
1	1500	870	0	650	2680
2	1200	1020	0	540	2790
3	800	1170	0	425	2900
4	500	1320	0	310	3010

			1
OTHER DETAILS		min.	max.
Jib length from to		1370	1825
Length of chassis incl. wheels	mm		1810
Width of chassis external	mm		1145
Width of chassis internal	mm		960
Clearance height, jib lowered	mm		1935
Clearance	mm		185
Ground clearance	mm		30
Load wheel	mm		150
Steering wheel	mm		175
Weight	ka		250

▼ FEATURES

- · Lightweight crane for occasional use
- The chassis and column can be dismantled into two parts by hand with simple tools for idle periods. An overhead crane or similar should be used to help.
- The chassis of the L1500 can handle a Euro pallet
- Double-acting pump
- · Delivery with CE declaration

The crane is designed to move under load. We recommend our Hydrobull industrial cranes for longer journeys – especially with a load or regular work, or for several lifting operations in succession.



Not the right machine? No problem!

Fill out our form on **www.hydrobull.de** and we will happily produce a custom transport solution for you. Link to www.hydrobull.de

Here, you can find more information incl. videos, photos etc.